

iQ300, free-standing
fridge-freezer with freezer at
bottom, 203 x 70 cm, Brushed
black steel anti-fingerprint, Total
noFrost
KG49NXXEA



Bottom freezer with hyperFresh Box to keep fruit and vegetables fresh for longer, plus noFrost for no more defrosting.

- ✓ No distance: Place your refrigerator directly against the wall or in a niche without a gap.
- ✓ noLimits: Full access to the drawers and easy removal for cleaning with the door open 90°.
- ✓ bigCapacity: More storage space for your groceries.
- ✓ bottleRack: Store your bottles safely and in easy reach.
- ✓ easyAccess: All your foods provided in view and within reach by movable glass shelves.

Features

Technical Data

Energy Efficiency Class (Regulation (EU) 2017/1369):	E
Average annual energy consumption in kilowatt hour per year (kWh/a) (EU) 2017/1369:	259 kWh/annum
Sum of volume of frozen compartments (EU 2017/1369):	108 l
Sum of volume of chill- and unfrozen compartments (EU 2017/1369):	330 l
Airborne acoustical noise emissions (EU 2017/1369):	40 dB(A) re 1pW
Airborne acoustical noise emission class (EU 2017/1369):	C
Built-in / Free-standing:	Free-standing
Number of compressors:	1
Number of independent cooling systems:	2
Width of the appliance:	700 mm
Height:	2030 mm
Depth of the product:	670 mm
Net weight:	83.5 kg
Door panel options:	Not possible
Door hinge:	Right reversible
Number of Adjustable Shelves in fridge compartment:	4
Shelves for Bottles:	Yes
Frost free system:	Fridge
Interior ventilator:	No
Reversible Door Hinge:	Yes
Length electrical supply cord:	240 cm
Noise level:	40 dB(A) re 1pW
Multi-Flow Air Tower:	Yes
Fast cooling switch:	Yes
:	Yes
Temperature Controlled Drawer:	No
Humidity Control Drawer:	Yes
Number of Door Bins - Refrigerator:	4
Door bin adjustability - Refrigerator:	Yes
Tilt-out door bins in fridge:	Yes
Gallon Storage:	Yes
Number of Gallon storage:	1
Motorized Shelf:	No
Material of the shelves:	Safety glass
Door opened indicator freezer:	No
Automatic motor-driven ice-maker:	No
Connection rating:	100 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50 Hz
Storage Period in Event of Power Failure (h):	16 h
Door panel options:	Not possible
Noise level:	40 dB(A) re 1pW
Energy Star Qualified:	No

Required cutout/niche size for installation (in): x
Dimensions of the packed product: 82.40 x 29.92 x 29.92
Net weight: 184.000 lbs
Gross weight: 198.000 lbs



**iQ300, free-standing
fridge-freezer with freezer at
bottom, 203 x 70 cm, Brushed
black steel anti-fingerprint, Total
noFrost
KG49NXXEA**

Features

Performance and consumption

- Energy Class EU19_EEK_D: E
- EU19_Unfrozen volume_D: 330 l
- Net Freezer Volume:
- EU19_Frozen volume_D: 108 l
- Annual Energy Consumption: EU19_Annual energy cons rd_D: 259 kWh/a
- Noise level: EU19_Noise emission_D: 40 dB

Design

- Doors black inox-antifingerprint, side panels cast iron
- Integrated vertical handle
- SoftStart LED light in fridge section

Comfort and Safety

- Twin LED electronic control, integrated in the door
- Optical and acoustic door open warning system
- Optical and acoustic warning system for malfunction of freezer compartment

Fridge Section

- multiAirflow-System
- 5 safety glass shelves of which 4 x easyAccess Shelf, extendable

Freshness System

- hyperFresh

Freezer Section


- 3 transparent freezer drawers
- Vario Zone - removable glass shelves for extra space

Technical Information

- Door right hinged, reversible hinging
- Height adjustable front feet, rolls in the back

iQ300, free-standing
fridge-freezer with freezer at
bottom, 203 x 70 cm, Brushed
black steel anti-fingerprint, Total
noFrost
KG49NXXEA

Dimensioned drawings



Appliance name	a	b	c	d	e	f	g	h
KGN 46 (Outer handle)	1860	700	670	590	740	1310	710	12
KGN 46 (Inner handle)	1860	700	670	590	710	1310	670	12
KGN 49 (Outer handle)	2030	700	670	590	740	1310	710	12
KGN 49 (Inner handle)	2030	700	670	590	710	1310	670	12

Description

a

Height

b

Width

c

Depth with door closed, without handle

d

Cabinet depth

e

Width with door opened to 90°

f

Depth with door opened, without handle

g

Depth with door closed, with handle

h

Air gap for installation in recess or fitted cabinet

measurements in mm