



Enjoy greater kitchen design freedom

Enjoy the multiple benefits of an induction hob that fits a 60cm cabinet with a built-in extractor for optimal airflow. The 600 Bridge Extractor Hob also has a Bridge function, allowing you to combine 2 cooking zones into one larger area.

Product Benefits & Features



Enjoy more kitchen planning freedom with integrated extractor

Kitchen Planning Freedom: Combine the speed, power and efficiency of an induction hob with integrated extraction to reduce placement restrictions on the hob.

Enjoy greater kitchen design freedom

Enjoy the multiple benefits of an induction hob that fits a 60cm cabinet with a built-in extractor for optimal airflow. The 600 Bridge Extractor Hob also has a Bridge function, allowing you to combine 2 cooking zones into one larger area.



Easily set the right power level with one touch control slider

Fast, easy, and precise control of all nine-level cooking zones with the Direct Touch Single Slider. With the PreciseHeat function, you can always set the perfect power level, down to a half level, for whatever you're cooking.



Enjoy a fresher kitchen atmosphere with less cooking odour

The included OdourClean Standard Carbon filter reduces kitchen odours. Easily replaced to keep your kitchen air fresh. Can also be replaced with the OdourClean Plus filter.*

*The stated lifespan is an estimate based on internal testing. Performance may vary depending on individual usage patterns and conditions; actual lifespan may be shorter or longer.



Automatic Extractor Control – adjusts as you cook

Automatic Extractor Control allows the hob to automatically switch on and regulate your hood according to your cooking activities, keeping your kitchen fresh while you focus on the food.

- Booster function
- Child safety lock function
- Bridge Function
- Hob²Hood funktion
- Pause function
- Automatic safety switch off
- Indicator for grease filter saturation
- Indicator for carbon filter saturation

Product Specification

Nordic_Series_and_Themes	600 FLEX	Recirculation Intensive, m ³ /h-2ndGen	585
Nordic_HB_FrameType_Colour	Frameless Square	Recirculation Max, m ³ /h-2ndGen	480
Dimensions WxD in mm	800x510	Recirc. sound power min, dB(A)	55
BI dimensions HxWxD in mm	225x750 - 780x490	Recirc. sound power max, dB(A)	71
Air outlet, mm	220	Cord length, m	1.5
Filter Type	Odour Clean Carbon Filter	Volt, V	220-240/400V2N
Grease filter, n° of	2	Bar code	7333394140100
OdourClean Standard Carbon filter	Included	Product Number Code	949 599 574
Radius cutting, mm	5/10 integrated		
LED colour	Red		
Total electricity loading	7350		
Energy efficiency class Hood	A+		
Fluid dynamic efficiency class	A		
Grease filter efficiency class	B		
Left Front - Power, W / Diam., mm,- 2nd Gen	2300/3200W/210mm		
Left Rear - Power, W / Diam., mm-2nd Gen	2300/3200W/210mm		
Right Front - Power, W / Diam., mm- 2nd Gen	1400/2500W/145mm		
Right Rear - Power, W / Diam., mm- 2nd Gen	1800/2800W/180mm		
Motor type	Brushless		
Extractor speeds	3+Intensive		
Recirculation Min, m ³ /h-2ndGen	250		

